

## TEST REPORT



REPORT NO.: CTNT2409240110101R

Product name: SLF UPLIFTING FACIALMICROCURRENTT LIGHT THERAPY

Model No.: 30064TAR

Applicant: Shenzhen Enjoy Technology Co., Ltd.

Test procedure: Entrustment Test

Shenzhen CTNT Testing Technology Co., Ltd.



This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@cnt-cert.com

Web: www.cnt-cert.com



**TEST REPORT****20 CCR § 1605.3(W) Battery Chargers and Battery Charger Systems.****Report Number.** ..... : CTNT2409240110101R**Date of issue** ..... : Oct.11,2024

**Name of Testing Laboratory** ..... Shenzhen CTNT Testing Technology Co., Ltd.  
Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street,  
Longgang District, Shenzhen, Guangdong, China  
**preparing the Report** ..... : Tel: 086-755-28680489  
E-mail: admin@ctnt-cert.com  
Web: www.ctnt-cert.com

**Applicant's name** ..... : Shenzhen Enjoy Technology Co., Ltd.**Address** ..... : 3/F, Building 7, Jinfo Industrial Zone, Baoan District, Shenzhen,  
China**Manufacturer** ..... : Shenzhen Enjoy Technology Co., Ltd.**Address** ..... : 3/F, Building 7, Jinfo Industrial Zone, Baoan District, Shenzhen,  
China**Test specification:****Standard** ..... : 20 CCR § 1605.3(W)(2) Energy Efficiency Standards for Small  
Battery Charger Systems.**Test procedure**..... : ☒CEC: California Appliance Efficiency Regulations - Small battery  
charger system (20 CA ADC § 1605.3(w)(2))**Non-standard test method**..... : N/A**Test Report Form No.**..... : CEC-BC-TRF**Test Report Form(s) Originator**.... : 1.0**Master TRF** ..... : CTNT**General disclaimer:**

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing CTNT Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the CTNT, responsible for this Test Report.

**Test item description** ..... : SLF UPLIFTING FACIALMICROCURRENTT LIGHT THERAPY**Model/Type reference**..... : 30064TAR, 30064**Trade Mark**..... : SLF**Ratings**..... : Input: 5V  1A  
Battery: 3.7V  800mAh

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com



<b>Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):</b>		
<b>Laboratory Name</b>	Shenzhen CTNT Testing Technology Co., Ltd.	
<b>Testing location/ address</b> .....	Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China	
<b>Tested by(Test Engineer)</b> .....	George Tian	George Tian
<b>Reviewed By(Supervisor)</b> .....	Oliver Long	Oliver Long
<b>Approved by(Chief Engineer)</b> .....	Flight Lee	Flight Lee
<b>Summary of testing:</b>		
<b>Tests performed (name of test and test clause):</b> Determination of the result includes consideration of measurement uncertainty from the test equipment and methods. A representative sample of the product covered by this report has been tested and with the requirements of 20 CCR § 1605.3(W)(2) Energy Efficiency Standards for Small Battery Charger Systems.	<b>Testing location:</b> Shenzhen CTNT Testing Technology Co., Ltd. Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China Tel: 086-755-28680489 E-mail: admin@cnt-cert.com Web: www.cnt-cert.com	
<b>General conditions for measurements:</b>		
<b>1.Test Room</b> The tests shall be carried out in a room that has an air speed close to the appliance under test of $\leq 0.5$ m/s. The ambient temperature shall be maintained at $(20 \pm 5)$ °C throughout the test.		
<b>2.Power supply</b> Where this standard is referenced by an external standard or regulation that specifies a test voltage and frequency, the test voltage and frequency so defined shall be used for all tests. Where the test voltage and frequency are not defined by an external standard, the test voltage and the test frequency shall be the nominal voltage and the nominal frequency of the country for which the measurement is being determined $\pm 1$ %.		
<b>3. Supply voltage waveform</b> The total harmonic content of the supply voltage when supplying the appliance under test in the specified mode shall not exceed 2 %; harmonic content is defined as the root-mean-square (r.m.s.) summation of the individual components using the fundamental as 100 %.		
<b>4. Power measurement accuracy</b> Precision measurement of energy consumption shall be made with a precision equal to the greater of 0.1 Watt-hour or 1% of full-scale measurement.		
<b>5. Testing Setup</b> Charge the battery with the UUT for the period specified by the UUT manufacturer as the time needed to		

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@cnt-cert.com

Web: www.cnt-cert.com