

TEST REPORT



REPORT NO.:CTNT240702022R

Product name: Twin Tub Washing Machine

Model No.: XPB45-45

Applicant: Ningbo BAIKE Electric Appliance Co., Ltd.

Test procedure: Entrustment Inspection

Shenzhen Zhongwei Testing Technology Co., Ltd.



This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@cnt-cert.com

Web: www.cnt-cert.com

TEST REPORT**§ 1605.1. Federal and State Standards for Federally Regulated Appliances.****20 CA ADC § 1605.1****Barclays Official California Code of Regulations****Report Number** CTNT240702022R**Date of issue** Jul.22,2024**Name of Testing Laboratory****preparing the Report**.....

Shenzhen Zhongwei Testing Technology Co., Ltd.

Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China

Tel: 086-755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com

Applicant's name..... Ningbo BAIKE Electric Appliance Co., Ltd.**Address** Xinsheng Road, Xipu Town, Cixi City, Zhejiang, China**Test specification:****Standard** 20 CA ADC § 1605.1(p)**Test procedure** 10 C.F.R. section 430.23(j) (Appendix J2 to subpart B of part 430).**Non-standard test method**..... N/A**Test Report Form No.**..... DOE- GJ -RRF**Test Report Form(s) Originator** 1.0**Master TRF** CTNT**General disclaimer:**

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing CTNT Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the CTNT, responsible for this Test Report.

Test item description

Twin Tub Washing Machine

Model/Type reference

XPB45-45, FP10871

Trade Mark

N/A

Manufacturer

Ningbo BAIKE Electric Appliance Co., Ltd.

Address

Xinsheng Road, Xipu Town, Cixi City, Zhejiang, China

Ratings

110-120V~ 60Hz 2.5A

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com

Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):		
Laboratory Name	Shenzhen Zhongwei Testing Technology Co., Ltd.	
Testing location/ address	Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China	
Tested by(Test Engineer)	Steve Zhou	Steve Zhou
Reviewed By(Supervisor)	Airan Lu	Airan Lu
Approved by(Chief Engineer)	Flight Lee	
Summary of testing:		
Tests performed (name of test and test clause): Determination of the result includes consideration of measurement uncertainty from the test equipment and methods. A representative sample of the product covered by this report has been tested and complies with the applicable requirements of 10 CFR 430.32(g) Clothes Washers	Testing location: Shenzhen Zhongwei Testing Technology Co., Ltd. Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China Tel: 086-755-28680489 E-mail: admin@ctnt-cert.com Web: www.ctnt-cert.com	
General conditions for measurements:		
1. Electrical energy supply 1.1 Supply voltage and frequency. Maintain the electrical supply at the clothes washer terminal block within 2 percent of 120, 120/240, or 120/208Y volts as applicable to the particular terminal block wiring system and within 2 percent of the nameplate frequency as specified by the manufacturer. If the clothes washer has a dual voltage conversion capability, conduct test at the highest voltage specified by the manufacturer. 1.2 Supply voltage waveform. For the combined low-power mode testing, maintain the electrical supply voltage waveform indicated in Section 4, Paragraph 4.3.2 of IEC 62301. If the power measuring instrument used for testing is unable to measure and record the total harmonic content during the test measurement period, total harmonic content may be measured and recorded immediately before and after the test measurement period. 2. Supply water Maintain the temperature of the hot water supply at the water inlets between 130°F (54.4°C) and 135°F (57.2°C), targeting the midpoint of the range. Maintain the temperature of the cold water supply at the water inlets between 55°F (12.8°C) and 60°F (15.6°C), targeting the midpoint of the range. 3. Water pressure		

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com