

Product name:

TEST REPORT



REPORT NO.:CTNT240510003R

Model No.: MLSC-01 Applicant:

Jieyang Airport District Xinan Anyou Electrical Appliance Factory

Folding washing machine

Test procedure: **Entrustment Inspection**



Tel: 0755-28680489 E-mail: admin@ctnt-cert.com Web: www.ctnt-cert.com

TEST REPORT

§ 1605.1. Federal and State Standards for Federally Regulated Appliances. 20 CA ADC § 1605.1

Barclays Official California Code of Regulations

Report Number.: CTNT240510003R

Date of issue: May.17,2024

Shenzhen Zhongwei Testing Technology Co., Ltd.

Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang

Name of Testing Laboratory

Street, Longgang District, Shenzhen, Guangdong, China

preparing the Report...... Tel: 086-755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com

Applicant's name......: Jieyang Airport District Xinan Anyou Electrical Appliance Factory

No. 38, East 1st Lane, Xinxiwei Road, Xizhai Village, Xinnan

Street, Jieyang Airport Economic Zone

Test specification:

Standard 20 CA ADC § 1605.1(p)

Non-standard test method.....: N/A

Test Report Form No.....: DOE- GJ -RRF

Test Report Form(s) Originator: 1.0

Master TRF.....: CTNT

General disclaimer:

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing CTNT Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the CTNT, responsible for this Test Report.

Test item description Folding washing machine

Model/Type reference: MLSC-01

Trade Mark Jieyang Airport District Xinan Anyou Electrical Appliance Factory

No. 38, East 1st Lane, Xinxiwei Road, Xizhai Village, Xinnan

Address:
Street, Jieyang Airport Economic Zone

Ratings: 110V-240V~ 50/60Hz

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489 E-mail: admin@ctnt-cert.com Web: www.ctnt-cert.com



| Laboratory Name | Shenzhen Zhongwei Testing Technology Co., Ltd. | |
|------------------------------|----------------------------------------------------------------------------------------------------------------------|------------|
| Testing location/ address:: | Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China | |
| Tested by(Test Engineer):: | Steve Zhou | Steve Zhon |
| Reviewed By(Supervisor):: | Airan Lu | Airan TECH |
| Approved by(Chief Engineer): | Flight Lee | CTNT |

Summary of testing:

Tests performed (name of test and test clause):

Determination of the result includes consideration of measurement uncertainty from the test equipment and methods.

A representative sample of the product covered by this report has been tested and complies with the applicable requirements of 10 CFR 430.32(g) Clothes Washers

Testing location:

Shenzhen Zhongwei Testing Technology Co., Ltd. Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China

Web: www.ctnt-cert.com

Tel: 086-755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com

General conditions for measurements:

1. Electrical energy supply

1.1 Supply voltage and frequency. Maintain the electrical supply at the clothes washer terminal block within 2 percent of 120, 120/240, or 120/208Y volts as applicable to the particular terminal block wiring system and within 2 percent of the nameplate frequency as specified by the manufacturer. If the clothes washer has a dual voltage conversion capability, conduct test at the highest voltage specified by the manufacturer. 1.2 Supply voltage waveform. For the combined low-power mode testing, maintain the electrical supply voltage waveform indicated in Section 4, Paragraph 4.3.2 of IEC 62301. If the power measuring instrument used for testing is unable to measure and record the total harmonic content during the test measurement period, total harmonic content may be measured and recorded immediately before and after the test measurement period.

2. Supply water

Maintain the temperature of the hot water supply at the water inlets between 130°F (54.4°C) and 135°F (57.2°C), targeting the midpoint of the range. Maintain the temperature of the cold water supply at the water inlets between 55°F (12.8°C) and 60°F (15.6°C), targeting the midpoint of the range.

3. Water pressure

Tel: 0755-28680489

E-mail: admin@ctnt-cert.com