

## TEST REPORT

REPORT NO.: CTNT230731002R



Product name: Ceramic toilet

Model No.: BP101

Applicant: ARRISEA SHOWER DOOR & HARDWARE, INC.

Test procedure: Entrustment Inspection

Shenzhen Zhongwei Testing Technology Co., Ltd.



|  |  |
|--|--|
| <b>TEST REPORT</b><br><b>20 CA ADC § 1605.3</b><br><b>Barclays Official California Code of Regulations</b>   |  |
| <b>Report Number.....:</b> CTNT230731002R<br><b>Date of issue.....:</b> Aug.09,2023  |  |
| <b>Name of Testing Laboratory preparing the Report.....:</b>   | Shenzhen Zhongwei Testing Technology Co., Ltd.<br>Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China<br>Tel: 086-755-28680489<br>E-mail: admin@ctnt-cert.com<br>Web: www.ctnt-cert.com |
| <b>Applicant's name.....:</b> ARRISEA SHOWER DOOR & HARDWARE, INC.<br><b>Address.....:</b> S El Monte CA 91733 US  |  |
| <b>Test specification:</b><br><b>Standard.....:</b> § 1605.3. State Standards for Non-Federally Regulated Appliances. (i) Plumbing Fixtures.<br><b>Test procedure.....:</b> 10 CFR 430, Appendix S of Subpart B. ASME A112.19.2-2018<br><b>Non-standard test method.....:</b> N/A  |  |
| <b>Test Report Form No.....:</b> CEC- MT-TRF<br><b>Test Report Form(s) Originator.....:</b> 1.0<br><b>Master TRF.....:</b> CTNT  |  |
| <b>General disclaimer:</b><br>The test results presented in this report relate only to the object tested.<br>This report shall not be reproduced, except in full, without the written approval of the Issuing CTNT Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the CTNT, responsible for this Test Report. |  |
| <b>Test item description.....:</b>   | Ceramic toilet   |
| <b>Model/Type reference.....:</b>  | BP101  |
| <b>Trade Mark.....:</b>  | ARRISEA  |
| <b>Manufacturer.....:</b>  | ARRISEA SHOWER DOOR & HARDWARE, INC.   |





This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com

|   |  |   |
|---|--|---|
| <b>Responsible Testing Laboratory (as applicable), testing procedure and testing location(s):</b>   |  |   |
| <b>Laboratory Name</b>  | Shenzhen Zhongwei Testing Technology Co., Ltd.   |   |
| <b>Testing location/ address.....:</b>  | Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China   |   |
| <b>Tested by(Test Engineer).....:</b>   | Oliver Long  |  |
| <b>Reviewed By(Supervisor).....:</b>  | Airan Lu   |  |
| <b>Approved by(Chief Engineer).....:</b>  | Flight Lee   |  |
|    |  |   |
| <b>Summary of testing:</b>  |  |   |
| <b>Tests performed (name of test and test clause):</b><br>Determination of the result includes consideration of measurement uncertainty from the test equipment and methods.<br>A representative sample of the product covered by this report has been tested and Ceramic toilet complies with the requirements of 20 CCR § 1605.3(i) Plumbing Fixtures.  | <b>Testing location:</b><br>Shenzhen Zhongwei Testing Technology Co., Ltd.<br>Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China<br>Tel: 086-755-28680489<br>E-mail: admin@cnt-cert.com<br>Web: www.cnt-cert.com |   |
| <b>General conditions for measurements:</b>   |  |   |
| The following requirements shall apply to all water closet tests:<br>a) The pressure- and flow-measuring apparatus employed for testing and the configuration of the water supply system shall be as shown in<br>i) Figure 11 for gravity and flushometer tank water closets; and<br>ii) Figure 12 for flushometer valve water closets.<br>b) The water supply system shall be standardized in accordance with Clause 7.1.5.1 or 7.1.5.2, as applicable.<br>c) The temperature of the water shall be 18 to 27 °C (65 to 80°F).<br>d) Water closets shall be tested at the test pressures specified in Table 5 or at the manufacturer's recommended minimum pressure. A test pressure greater than 550 kPa (80 psi) shall not be used.<br>e) The specimen shall be placed on a flat and level or plumb surface, with the outlet and trap clear.<br>f) The specimen shall discharge to atmosphere.<br>Tests shall be conducted in the sequence specified in Table 5 |  |   |
| <b>Possible test case verdicts:</b>   |  |   |
| - test case does not apply to the test object.....: N/A   |  |   |
| - test object does meet the requirement.....: P (Pass)  |  |   |
| - test object does not meet the requirement.....: F (Fail)  |  |   |

This report may not be reproduced in part without permission to avoid ambiguous interpretation.

This report can be checked and verified in the following ways.

Tel: 0755-28680489

E-mail: admin@cnt-cert.com

Web: www.cnt-cert.com