

TEST REPORT





Product name:	1.5 m two plug one double USB with light board
Model No.:	12636-2A
Applicant:	SHEN ZHEN JING CHANG DA NONFERROUS METALS CO., LTE
дрисант.	OFFICIAL STING CHAING DA NONE ENROUGHETALS CO., LTL
est procedure:	Entrustment Test





TEST REPORT

§ 1605.1. Federal and State Standards for Federally Regulated Appliances. 20 CA ADC § 1605.1

Barclays Official California Code of Regulations

Report Number...... CTNT2410110100201R

Date of issue.....: Dec.03,2024

Shenzhen Zhongwei Testing Technology Co., Ltd

Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street,

Name of Testing Laboratory

Longgang District, Shenzhen, Guangdong, China

preparing the Report....: Tel: 086-755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com

Applicant's name...... SHEN ZHEN JING CHANG DA NONFERROUS METALS CO., LTD

518115

Test specification:

Standard.....: 20 CCR §° 1605.1

Test procedure......: ⊠ CEC: § 1605.1. Federal and State Standards for Federally

Regulated Appliances. (u) External Power Supplies.

Non-standard test method.....: N/A

Test Report Form No.....: CEC-BC-EPS

Test Report Form(s) Originator....: 1.0

Master TRF.....: CTNT

General disclaimer:

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing CTNT Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the CTNT, responsible for this Test Report.

Test item description...... 1.5 m two plug one double USB with light board

Model/Type reference.....: 12637-2A, 12637-2+C, 12636-2A

Trade Mark....: N/A

Manufacturer.....: SHEN ZHEN JING CHANG DA NONFERROUS METALS CO., LTD

Input: 120V~, 60Hz

Output: 120V~, 5V— 1A、 5V— 1A



Shenzhen Zhongwei Testing Technology Co., Ltd	
Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China	
Schale zeng	Schale zeng
Oliver Long	Dave TING TECK
Flight Lee	CTNT

The tests shall be carried out in a room that has an air speed close to the unit under test (UUT) of \leq 0.5 m/s. The ambient temperature shall be maintained at 20 \pm 5°C throughout the test..

2.Power supply

If the UUT is intended for operation on AC line-voltage input in the United States, it shall be tested at 115 V at 60 Hz. If the UUT is intended for operation on AC line-voltage input but cannot be operated at 115 V at 60 Hz, it shall not be tested. The input voltage shall be within ±1 percent of the above specified voltage.

3. Supply voltage waveform

The THD of the supply voltage when supplying the UUT in the specified mode must not exceed 2%, up to and including the 13th harmonic

4. Power measurement accuracy

Precision measurement of energy consumption shall be made with a precision equal to the greater of 0.1 Watt-hour or 1% of full-scale measurement.

Possible test case verdicts:	
- test case does not apply to the test object:	N/A
- test object does meet the requirement:	P (Pass)
- test object does not meet the requirement:	F (Fail)
Declared data:	
Nameplate input voltage(V):	120V~
Nameplate inputfrequency(Hz):	60Hz
Nameplate output voltage(V):	120V~、5V—、5V—
Nameplate output current(A):	8A、1A、1A
Nameplate output power(W):	1000W、5W、5W

Testing:

Tel: 0755-28680489

E-mail: admin@ctnt-cert.com

Web: www.ctnt-cert.com