

TEST REPORT

REPORT NO.: CTNT2412270010101R

Product name: MINIPC

Model No.: MS-01-S1390

Applicant: MICRO COMPUTER (HK) TECH LIMITED

Test procedure:

Entrustment test

Shenzhen CTNT Esting Chnology Co., Ltd.

This report may not be reproduced in part without permission to avoid ambiguous interpretation. This report can be checked and verified in the following ways. Tel: 0755-28680489 E-mail: admin@ctnt-cert.com Web: www.ctnt-cert.com

Page 2 of 12 Report No.CTNT2412270010101R TEST REPORT § 1605.3. State Standards for Non-Federally Regulated Appliances. 20 CA ADC § 1605.3 **Barclays Official California Code of Regulations** Report Number.....: CTNT2412270010101R Date of issue.....: Jan.03.2025 Shenzhen CTNT Testing Technology Co., Ltd. Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Name of Testing Laboratory Street, Longgang District, Shenzhen, Guangdong, China preparing the Report..... : Tel: 086-755-28680489 E-mail: admin@ctnt-cert.com Web: www.ctnt-cert.com Applicant's name..... MICRO COMPUTER (HK) TECH LIMITED FLAT/RM 18, 28/F, Shui On Centre, 6-8 Harbour Road, Address..... Waterfront Wan Chai, Hong Kong Manufacturer's name...... MICRO COMPUTER (HK) TECH LIMITED FLAT/RM 18, 28/F, Shui On Centre, 6-8 Harbour Road, Address..... Waterfront Wan Chai, Hong Kong Test specification: Standard.....: 20 CA ADC § 1605.3 Test procedure.....: 20 CA ADC § 1605.3(v) Non-standard test method.....: N/A Test Report Form No.....: CEC- COM-TRF Test Report Form(s) Originator.....: 1.0 Master TRF.....: CTNT General disclaimer: The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing CTNT Testing Laboratory. The authenticity of this Test Report and its contents can be verified by contacting the CTNT, responsible for this Test Report. Test item description.....: MINIPC Model/Type reference.....: MS-01-S1390, MS-01-S1260, MS-01-S1290, MS-01********** Trade Mark.....: N/A Input: 100-240V~ 50/60Hz 2.5A Ratings..... Output: 19.0V-9.47A 179.93W This report may not be reproduced in part without permission to avoid ambiguous interpretation. This report can be checked and verified in the following ways.

Tel: 0755-28680489 E-mail: admin@ctnt-cert.com Web: www.ctnt-cert.com

<u>CTNT</u>®

Page 3 of 12

Report No.CTNT2412270010101R

Laboratory Name:	Sher	Shenzhen CTNT Testing Technology Co., Ltd.		
Testing location/ address:	Hen	Room 1A106, 1/F., No.109, Lijia Road, Henggang, Henggang Street, Longgang District, Shenzhen, Guangdong, China		
Tested by(Test Engineer):	Scha	ale Zeng	Schale zeng	
Reviewed By(Supervisor):	Oliver Long		Oliver Long	
Approved by(Chief Engineer):	Flight Lee		CTNT	
Summary of testing:		J.S.	TOPROVED	
Tests performed (name of test and test clau	se):	Testing location	:	
Determination of the result includes consideration of measurement uncertainty from the test equipment and methods. A representative sample of the product covered bythis report has been tested and computers complies with the requirements of1605.3 (v)		Shenzhen CTNT Testing Technology Co., Ltd.		
		Room 1A106, 1/F., No.109, Lijia Road, Henggang,		
		Henggang Street, Longgang District, Shenzhen,		
		Guangdong, China		
		Tel: 086-755-28680489		
		E-mail: admin@ctnt-cert.com		
		Web: www.ctnt-cert.com		

General conditions for measurements:

1.Test Room

The tests shall be carried out in a room that has an air speed close to the appliance under test of ≤ 0.5 m/s. The ambient temperature shall be maintained at (20 ± 5) °C throughout the test.

2.Power supply

Where this standard is referenced by an external standard or regulation that specifies a test voltage and frequency, the test voltage and frequency so defined shall be used for all tests. Where the test voltage and frequency are not defined by an external standard, the test voltage and the test frequency shall be the nominal voltage and the nominal frequency of the country for which the measurement is being determined ± 1 %.

3. Supply voltage waveform

The total harmonic content of the supply voltage when supplying the appliance under test in the specified mode shall not exceed 2 %; harmonic content is defined as the root-mean-square (r.m.s.) summation of the individual components using the fundamental as 100 %.

4. Power measurement accuracy

Precision measurement of energy consumption shall be made with a precision equal to the greater of 0.1 Watt-hour or 1% of full-scale measurement.

This report may not be reproduced in part without permission to avoid ambiguous interpretation. This report can be checked and verified in the following ways.

Tel: 0755-28680489 E-mail: admin@ctnt-cert.com Web: www.ctnt-cert.com